


K-LOC DISCS
G M C DRY
KGS Swiflex® QS
1015
Backing

Special KGS K-LOC system.

Recommended speed

Max. 45m/s.

Application

For grinding and polishing without water on granite, marble, concrete, composites and terrazzo.

Properties

Grit 60-400	Metal bond
Grit 500-3000	Resin bond

KGS Swiflex® QS K-LOC ø25mm

COLOUR/GRIT	CODE
60	1021.0600811
120	1021.0600812
200	1021.0600813
400	1021.0600814
500	1021.0600825
1500	1021.0600826
3000	1021.0600827

KGS Swiflex® QS K-LOC ø50mm

COLOUR/GRIT	CODE
60	1021.0600911
120	1021.0600912
200	1021.0600913
400	1021.0600914
500	1021.0600915
1500	1021.0600926
3000	1021.0600927

KGS Swiflex® QS K-LOC ø75mm

COLOUR/GRIT	CODE
60	1021.0601011
120	1021.0601012
200	1021.0601013
400	1021.0601014
500	1021.0601015
1500	1021.0601026
3000	1021.0601027


Accessories
KGS Swiflex® K-LOC back-up pads

ø mm	CODE
ø25	8851.10038
ø35	8851.00477
ø45	8851.10036
ø70	8851.10035


KGS® adapter

TYPE	CODE
½" R ext.-ø6mm	8851.00071
M14 int.-ø6mm	8851.00098

